



	 Air MAX	 Air SE	 ArGo	 Solo III	 Solo II MAX	 Solo II
DEVICE TYPE	PORTABLE	PORTABLE	PORTABLE	PORTABLE	PORTABLE	PORTABLE
DEVICE WEIGHT	160 GRAMS	103 GRAMS	97 GRAMS	280 GRAMS	210 GRAMS	210 GRAMS
DEVICE HEIGHT	128 MM	122 MM	93 MM	130 MM	113 MM	113 MM
RUN TIME	UP TO 135 MINUTES PER CHARGE	UP TO 80 MINUTES PER CHARGE	UP TO 90 MINUTES PER CHARGE	UP TO 180 MINUTES PER CHARGE	UP TO 180 MINUTES PER CHARGE	UP TO 180 MINUTES PER CHARGE
WPA COMPATIBILITY	14MM & 19MM; 14MM INCLUDED	14MM & 19MM	14MM & 19MM	14MM & 19MM; 14MM INCLUDED	14MM & 19MM; 14MM INCLUDED	14MM & 19MM
GLASS POD SYSTEM	AIR / SOLO GLASS AROMA TUBES	AIR / SOLO GLASS AROMA TUBES	ARGO GLASS AROMA TUBES	XL GLASS AROMA TUBES & AIR / SOLO GLASS AROMA TUBES	AIR / SOLO GLASS AROMA TUBES	AIR / SOLO GLASS AROMA TUBES
ISOLATED AIR PATH	YES	YES	YES	YES	YES	YES
HEAT MODE	SESSION	SESSION	SESSION	SESSION + ON DEMAND	SESSION	SESSION
OVEN	HYBRID: 75% CONVECTION, 25% CONDUCTION	HYBRID: 75% CONVECTION, 25% CONDUCTION	HYBRID: 70% CONVECTION, 30% CONDUCTION	HYBRID: 80% CONVECTION, 20% CONDUCTION	HYBRID: 75% CONVECTION, 25% CONDUCTION	HYBRID: 70% CONVECTION, 30% CONDUCTION
HEATING ELEMENT	SILICA-FREE RAPID-HEATING CERAMIC	SILICA-FREE RAPID-HEATING CERAMIC	SILICA-FREE CERAMIC	SILICA-FREE INSTANT-HEATING CERAMIC CONVECTION TECHNOLOGY	SILICA-FREE RAPID-HEATING CERAMIC	SILICA-FREE CERAMIC
HEAT UP TIME	< 60 SECONDS	< 60 SECONDS	~ 90 SECONDS	5-15 SECONDS	< 30 SECONDS	< 30 SECONDS
TEMPERATURE DISPLAY	DIGITAL: CELSIUS & FAHRENHEIT	ANALOG	DIGITAL: CELSIUS & FAHRENHEIT	DIGITAL: CELSIUS & FAHRENHEIT	DIGITAL: CELSIUS & FAHRENHEIT	DIGITAL: CELSIUS & FAHRENHEIT
TEMPERATURE CONTROL	1 & 10 DEGREE INCREMENTS	5 PRE-SET TEMPERATURES	1 & 10 DEGREE INCREMENTS	1 & 10 DEGREE INCREMENTS + PROGRAMMABLE PRESETS	1 & 10 DEGREE INCREMENTS	1 & 10 DEGREE INCREMENTS
TEMPERATURE RANGE	50-220C / 122-428F	180-210C / 356-410F	50-220C / 122-428F	50-220C / 122-428F	50-220C / 122-428F	50-220C / 122-428F
POWER	REMOVABLE HIGH CAPACITY 26650 LI-ION BATTERY	REMOVABLE HIGH CAPACITY 18650 LI-ION BATTERY	REMOVABLE HIGH CAPACITY 18650 LI-ION BATTERY	DUAL-CELL HIGH CAPACITY 21700 BATTERY	DUAL-CELL HIGH CAPACITY 18650 BATTERY	DUAL-CELL HIGH CAPACITY 18650 BATTERY
CHARGING	USB-C Charger (5v 2A)	5V MICRO-USB	5V MICRO-USB	USB-C (5v, 3A)	USB-C (5v, 3A)	FAST 12V DC
USE WHILE CHARGING	YES	YES	YES	YES	YES	YES
POWER ON DELAY	2-8 SECONDS	PRESET - 2 SECONDS	2-8 SECONDS	2-8 SECONDS	2-8 SECONDS	4-8 SECONDS
CUSTOM SESSION SETTINGS	YES	YES	YES	YES	YES	YES
AUTOMATIC DISPLAY & CONTROL INVERSION	DISPLAY INVERSION	NO	NO	DISPLAY & CONTROL INVERSION	DISPLAY & CONTROL INVERSION	NO
DARK MODE	YES	NO	NO	NO	YES	NO
AUTO SHUT OFF TIMER	5-15 MINUTES	PRESET - 10 MINUTES	5-15 MINUTES	5 - 20 MINUTES	5-15 MINUTES	5-15 MINUTES
MAX BOWL SIZE	0.3 GRAMS	0.3 GRAMS	0.3 GRAMS	0.5 GRAMS	0.3 GRAMS	0.3 GRAMS
PUSH-TOP PROTECTION	NO	NO	YES	NO	NO	NO
COLOR LEDS	N/A	N/A	N/A	N/A	N/A	N/A
REMOTE	N/A	N/A	N/A	N/A	N/A	N/A
QUIET 3-SPEED FAN	N/A	N/A	N/A	N/A	N/A	N/A
AIR FILTER	N/A	N/A	N/A	N/A	N/A	N/A
WHIP SYSTEM	N/A	N/A	N/A	N/A	N/A	N/A
BAG SYSTEM	N/A	N/A	N/A	N/A	N/A	N/A